

J9F SERIES



MODULAR JACK CONNECTORS: 4 PORT (2x2 STACKED) RJ45, RIGHT ANGLE PCB MOUNT, NON-SHIELDED

Features:

- Top performance for high speed networking, voice and data applications
- Meet FCC PART 68, Subpart F requirements
- Applications: Telecommunications, Broadcast, Data Products
- RoHS Compliant



Specifications:


Insulator Material	PBT or Nylon
Contact Material	Phosphor Bronze
Contact Plating	Gold Plating on contact area and Tin Plating on tails with Nickel underplating all over
Current Rating	1.5 amps @25°C
Voltage Rating	125 V AC
Contact Resistance	20 milliohms maximum
Dielectric Withstanding Voltage	1000 V AC
Insulation Resistance	500 megaohms minimum
Durability	750 cycles minimum
Operating Temperature	-40°C to +85°C
Wave Soldering Process	260°C ± 5°C, 5~10 Seconds

Ordering Code:

EXAMPLE PART NUMBER: J9F048822P00021

SERIES: RJ MODULAR JACK

HOUSING TYPE: 9F-



NO. OF PORTS: 04 - 4 PORT

NO. OF CONTACTS PER PORT: 88 - 8P8C

CONTACT PLATING:
 2 - GOLD FLASH
 3 - 15 MICROINCHES OF GOLD
 6 - 30 MICROINCHES OF GOLD
 9 - 50 MICROINCHES OF GOLD

CONTACT TAIL TYPE: 2 - RIGHT ANGLE PCB

HOUSING MATERIAL:
 P - PBT
 N - NYLON

MOUNTING OPTIONS:
 1 - BOARD LOCKS

PORT TYPE:
 2 - TWO ROWS OF PORTS

SHIELDING:
 0 - NO SHIELD

RIGHT LED COLOR:
 0 - NO LED

LEFT LED COLOR:
 0 - NO LED