



BACK MOUNTED*

	A	B	C	D	E	F	G	H
9 STD / 15 H.D.	0.984 [24.99]	0.806 [20.47]	0.609 [15.46]	0.492 [12.50]	0.530 [13.46]	0.420 [10.67]	0.210 [5.33]	0.223 [5.66]
15 STD / 26 H.D.	1.312 [33.32]	1.134 [28.80]	0.937 [23.79]	0.656 [16.66]	0.858 [21.79]	0.420 [10.67]	0.210 [5.33]	0.223 [5.66]
25 STD / 44 H.D.	1.852 [47.04]	1.674 [42.52]	1.477 [37.51]	0.926 [23.52]	1.398 [35.51]	0.420 [10.67]	0.210 [5.33]	0.223 [5.66]
37 STD / 62 H.D.	2.500 [63.50]	2.326 [59.08]	2.129 [54.07]	1.250 [31.75]	2.050 [52.07]	0.420 [10.67]	0.210 [5.33]	0.223 [5.66]
50 STD / 78 H.D.	2.406 [61.11]	2.218 [56.34]	2.021 [51.32]	1.203 [30.54]	1.895 [48.12]	0.555 [14.10]	0.278 [7.05]	0.358 [9.08]

TOLERANCE = ±0.005 inch

MAX. PANEL THICKNESS*:**

- = (0.060" when using CDF/HDF/SDF Series)
- = (0.050" when using 09/15 sized SF67 & SFP67 Series Sealing Flanges with 160-067 Series IP67 Panel Mounting Kits)
- = (0.041" when using 25 sized SF67 & SFP67 Series Sealing Flanges with 160-067 Series IP67 Panel Mounting Kits)

MAX. JACK POST // STANDOFF HEIGHT = 0.189"

MAX. JACK POST TORQUE:

- = (40 in-oz maximum recommended for CDF/HDF/SDF Series // Gasket compression nominally ~0.010")
- = (20 in-oz maximum recommended when using SF67 & SFP67 Series Sealing Flanges with 160-067 Series IP67 Panel Mounting Kits // Gasket compression negligible)

NOTES:

*THESE DIMENSIONS ARE RECOMMENDED BUT MAY NOT SUIT ALL APPLICATIONS IF YOU HAVE ANY QUESTIONS REGARDING THESE DIMENSIONS FOR USE FOR AN IP67 APPLICATION PLEASE REACH OUT TO ENG@NORCOMP.NET

**USE NORCOMP'S SF67 SERIES IP67 SEALING FLANGES (NOT REQUIRED IF USING NORCOMP CDF/HDF/SDF SERIES FLANGED DSUBS)

***CALCULATIONS BASED ON [DSUB MATING DISTANCE PDF](#)

RoHS COMPLIANT

UNITS = inch[mm]

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

03/17/2020

NorComp

SCALE:

NTS

SHEET

OF

1

1

REV

5

DWG NO.

IP67 PANEL CUTOUT D-SUB